

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : A61F 9/00, G02C 11/00	A1	(11) International Publication Number: WO 94/03135 (43) International Publication Date: 17 February 1994 (17.02.94)
(21) International Application Number: PCT/US93/07488 (22) International Filing Date: 9 August 1993 (09.08.93) (30) Priority data: 07/927,342 10 August 1992 (10.08.92) US 07/976,274 13 November 1992 (13.11.92) US (71) Applicant: THE SCHEPENS EYE RESEARCH INSTITUTE [US/US]; 20 Staniford Street, Boston, MA 02114 (US). (72) Inventor: BERTERA, James, H. ; 4 Longfellow Place, #3011, Boston, MA 02114 (US). (74) Agents: LIEPMANN, W., Hugo et al.; Lahive & Cockfield, 60 State Street, Boston, MA 02109 (US).		(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: METHOD AND APPARATUS FOR INTRODUCING FLUID MATERIAL INTO AN EYE



(57) Abstract

A spectacle-like device (20) mounts a system of pump elements (14) that can project droplets of liquid onto a wearer's eye. A reservoir (12) of the liquid and an electrical pump-controlling circuit (16) are mounted on the spectacle frame (20) for operation with the pump elements (14).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

METHOD AND APPARATUS FOR INTRODUCING FLUID MATERIAL INTO AN EYE

5 Background

This invention relates to devices for applying fluid to biological tissue and more particularly to apparatus which instills an aqueous solution into the eye. The invention has application, for example, as an unobtrusive and automatic device for
10 introducing artificial tear fluid to relieve the discomfort and potential ocular damage caused by chronic dry eye condition, i.e., lachrymal deficiency. The invention also provides a corresponding method.

Many people suffer from a lack of eye moisture, resulting in discomfort and
15 ocular damage. Even though available artificial tear solutions increase eye moisture and relieve discomfort, the application of an artificial tear solution provides only temporary relief. As a result, dry eye sufferers commonly apply artificial tear solution to their eyes repeatedly within the span of a day. The burden and interruption caused by frequent application of eye drops is a disincentive to applying the required dosages
20 and to maintaining the proper moisture levels.

In addition to treating lachrymal deficiency, there is need for a device that introduces fluid into an eye to administer therapeutic agents that treat conditions such as corneal ulcerations. In these cases, an active medicinal agent is dissolved into a
25 volume of fluid and administered to the eye. The applied fluid washes over the outer surface of the eye and thereby distributes the agent across the corneal surface. Introducing fluids having active medical ingredients to an eye requires careful control of the quantity of fluid administered. It generally is difficult, with the manual application of the fluid with an eye dropper, to control the number of drops introduced
30 to the eye.

Some eye droppers exist that have a fluid chamber with a threaded piston that screws within a correspondingly threaded cylinder. The piston can be advanced within the cylinder by a selected number of threads and then held in position. By
35 advancing the piston a pre-determined amount, a corresponding predetermined volume of fluid is expelled from the chamber. Due to the mechanics involved, these devices are usually bulkier and more cumbersome than typical eyedroppers. This unwieldiness adds to the disincentive of a patient to apply a fluid.

-2-

Other devices have been developed that deliver fluid to an eye. These devices typically work by pumping fluid from a reservoir through a tube that has its distal end positioned adjacent to the eye. In some applications, the tube is surgically implanted under the skin; it begins at a fluid reservoir positioned, for example, at the lumbar region and ends adjacent the eye. These devices are cumbersome and invasive, and the mechanism needed to pump the fluid through the length of the tube is bulky and requires a heavy and bulky power source. Furthermore, control problems result from having to pump fluid to the eye through the relatively lengthy tube. Also, fluid flow within the tube can be disrupted by patient movement, and by inadvertent pinching or collapsing of the tube.

Portable eye irrigation systems have been developed which require the user to carry relatively cumbersome pump equipment and which offer limited flexibility and comfort. "Mechanical Devices", The Preocular Tear Film and Dry Eye Syndromes, Spring 1973, Vol 13, No. 1, describes several such devices. Typically, the prior systems have a single fluid outlet disposed in contact with each eye. Some systems have controls that provide adjustment to the delivered fluid volume, and some systems provide continuous irrigation.

Therefore, it is an object of this invention to provide apparatus which administers fluid to the eye in a controlled and compact fashion. An apparatus according to this object can offer a user comfort while delivering droplets or therapeutic mist to the eye.

It is another object of the present invention to provide an apparatus that is convenient to use for the sustained introduction of fluid into a person's eye.

It is a further object of the invention to provide an apparatus which provides relatively precise control over the quantity and frequency of fluid administered into an eye.

Another object of this invention is to provide an apparatus for introducing fluid into an eye and that is non-invasive and visually non-obstructive.

A further object of this invention is to provide an apparatus for introducing fluid into an eye with relatively low impact of fluid on the corneal surface of the eye.

Yet another object of this invention is to provide a facile method and apparatus for introducing fluid and therapeutic agents into an eye.

-3-

Other objects of the invention will be apparent from the description that follows.

5 Summary of the Invention

The invention achieves the aforementioned objectives by providing, in one aspect, a device that introduces fluid to the corneal surface of the eye by having a pump element that projects droplets of the desired solution onto the eye. The pump
10 element is fluidically coupled to a container of the solution. The coupled pump element and fluid container mount to a spectacle frame, and hence are positioned proximal to and in front of the eye. The pump element has a fluid outlet disposed adjacent to the eye and oriented so that fluid expelled from the outlet is directed at the corneal surface. A control circuit actuates the pump element to propel the solution from the
15 fluid outlet into the air for travel to the eye.

A device for introducing fluid onto an eye as described above has application in relieving conditions involving lacrimal deficiency and in administering therapeutic fluids, i.e., drugs, to the surface of the eye. An artificial tear solution or a medicated
20 fluid can be placed within the fluid container, and the user can activate the apparatus to deliver dosages of the fluid as selected with the control circuit. In particular, fluid from the container can be delivered to the pump for spraying onto the eye in minute increments. Upon actuation by a control signal generated by the control circuit, the pump element in one aspect delivers picoliter volumes of fluid to the eye. With a
25 preferred type of pump, each picoliter volume is individually expelled from the fluid outlet as a discrete burst, spray or droplet of fluid. The fluid is ejected as a succession of droplets that travel through the air directly onto the corneal surface of the eye. Since the fluid is delivered in minute increments, i.e., picoliters, the invention attains fine control over the volume of fluid introduced into the eye.

30

The provision of both the applicator pump and the fluid outlet on a spectacle frame, in accord with the invention, attains superior performance. Further, the preferred pump element is immediately adjacent the fluid outlet, which enhances control of the droplet volume and discharge force. Also, the provision of both the
35 pump and the outlet structure mounted together on the spectacle frame attains a high level of user convenience. It enables a person to use the device, and conversely remove it, with utmost ease. In a preferred embodiment, a reservoir of the fluid and the control circuit are also mounted on the spectacle frame, for further user convenience. The pump projects droplets into air for travel, unguided, to an ocular

-4-

surface. The droplets preferably occur in succession with a controller selecting the duration or repetition rate.

5 A further feature of the invention is that the pump element preferably is a thermal expansion jet-type pump. The invention provides this type of pump combined with the liquid outlet in an exceedingly small and light-weight structure. An additional feature is a diaphragm-type member in the pump element to separate and thereby isolate, at least in part, the liquid being discharged to the wearer's eye from the liquid being heated for thermal expansion in the pump. Pumps of the thermal
10 expansion jet-type are known for use in computer printers of the ink-jet type: U.S. Patent No. 4,500,895 discloses one ink jet pump. Other thermal pumps can utilize laser energy to heat and expand working fluids, therapeutic fluids or absorbing elements.

15 It is also an advantage of this invention that patient safety is increased by providing a structure that is not surgically implanted and that does not come in physical contact with the eye. By the use of a pump that projects the liquid from an outlet, the invention removes the need to place fluid delivery tubes in contact with any tissue of the wearer, particularly tissue of the eye. The invention enhances patient
20 safety and convenience by using soft flexible extension tubes to connect the fluid container to the pump element. The structure also imposes minimal restriction on the patient's field of view.

In another aspect, multiple fluid outlets, typically each with a separate pump,
25 circumferentially surround the lens aperture of the eyeglasses to provide generally uniform fluid treatment to the eye. The fluid outlets disposed on the eyeglasses permit the unguided transmittal of fluid from the outlet through the air to the eye. Accordingly, the non-contact nature of the invention reduces the chance of infection as compared to devices disposed in contact with the eye. Such a device according to
30 the invention is therefore useful in surgery requiring eye irrigation. Multiple pump outlets can surround a singular eye aperture, in this aspect, to efficiently irrigate the eye.

The invention also enhances the control for applying liquid to the eye. In
35 some aspects according to the invention, both the rate of repetition and the volume of fluid droplets propelled from the pumps are programmable and controllable.

In still other aspects, a method is provided for introducing fluid to the eye. An electrically controlled pump and fluid outlet are mounted to typical spectacle-like

-5-

frames. The pump and fluid outlet are in fluid communication with a container which holds the fluid for application to the eye. An electrical signal is generated to activate the pump, thereby expelling the fluid from the container through the outlet and to the eye. The pump, in one practice of the invention, operates by pressurizing a fluid
5 container causing controlled and pressurized ejection of fluid from the outlet into the air and toward the eye. In this aspect, the fluid outlet is preferably a tapered tube with a jet or nozzle-like orifice placed near the eye, but not in contact with it.

In yet another aspect, the container holding the fluid is pressurized and
10 maintained by micro-valves. Micro-valves, preferably at the fluid outlet orifice, control the release of fluid from the pressurized container in response to controlled electrical signals. Micro-valves employ piezoelectric crystals or shape-memory alloys, like TiNi.

15 In still other aspects, slender supports or stalks carry the pump element or micro-valve. A flexible stalk supporting a pump or micro-valve according to the invention greatly aids the control and delivery of fluid to an eye. For example, one stalk per eye affixed to a spectacle frame and carrying a small pump or micro-valve element can effectively and controllably irrigate the eye. In a separate configuration, a
20 support structure with a stalk operates as a medicinal dispenser, a precise drug or chemical applicator, or a mist irrigator during surgical procedures.

These and other advantages of the invention will be more clearly understood by reference to the following detailed description and attached drawing, in which like
25 reference numbers refer to like elements.

Brief Description of the Drawing

FIGURE 1 is a pictorial view of apparatus for introducing fluid to an eye and
30 embodying features of the invention.

FIGURE 2 is a pictorial view of fluid being introduced to an eye by a method embodying features of the invention.

35 FIGURES 3 and 4 are simplified diagrammatic side and enlarged front views respectively of a pump for practice of the invention.

FIGURE 5 shows a succession of pictorial views A through E illustrating operation of a thermal expansion jet-type pump in the apparatus of FIGURE 1.

FIGURE 6 is a pictorial view, partly disassembled, of an alternative apparatus for introducing fluid to an eye according to further features of the invention.

5 FIGURES 7 and 8 are views similar to FIGURES 1 and 5, respectively, of a further embodiment of the invention; and FIGURE 7A is a detail view of a duct for use therein.

10 FIGURE 9 is a pictorial view of a further embodiment of the invention, for delivering liquid to an eye during, for example, a surgical procedure.

Description of Illustrated Embodiments

One instillation device 10 according to the invention, shown in FIGURE 1, has
15 a pump mounted on a spectacle-like frame and which can project droplets of fluid onto the corneal surface of an eye. A patient wears the illustrated device like conventional spectacles, i.e., a pair of eyeglasses. The illustrated device 10 has a container 12 that holds a supply of fluid, an array of pumps 14 that project the fluid, a control module 16 that actuates the pumps 14, and fluid ducts 18 that fluidically couple the pumps 14 to
20 the container 12. All of these elements are carried on a spectacle-like support frame 20. The frame 20 can mount optical lenses and hence serve also as a pair of eyeglasses.

The instillation device 10 can apply, among other fluids, moisturizing or
25 medicating liquid to the topical surface of a patient's eye. The container 12 holds a supply of liquid and fluidically connects with the pumps 14 by way of the fluid ducts 18. The ducts 18, as illustrated, preferably conform to the structure of the spectacle-like frame 20. The control module 16 produces electrical control signals that actuate the pumps 14 to expel fluid. Each pump 14 electrically connects to the control module
30 16 to receive a control signal. Each illustrated pump 14 is a thermal expansion jet-type pump.

The device 10 depicted in FIGURE 1 is worn by the patient like conventional
eye glasses. The frame 20 has an eye-piece 26 that rests on the bridge of the patient's
35 nose and is held in position by two temple members that supportingly engage the patient's ears. As further shown in FIGURE 1, a plurality of pumps 14 are disposed about the rim of each eye-piece 26 of the frame 20. Preferably the arrangement of the pumps 14 circumferentially surrounds the eyeglass aperture to apply fluid from the container 12 substantially uniformly over the surface of the eye. The frame 20 locates

-7-

the pumps 14 adjacent to and spaced in front of the patient's eyes so that the pumps can project fluid into the air and toward the eye, as FIGURE 2 shows. In the embodiment shown in FIGURE 1, the eyepiece typically is positioned between 1 cm and 7 cm in front of the eye of the patient.

5

As shown in FIGURE 2, each pump 14 preferably is oriented to direct liquid to a selected location or region on the outer corneal surface. The control module 16 actuates each pump 14 to expel fluid at a specified rate and volume, as explained further hereinafter.

10

Returning to FIGURE 1, the illustrated container 12 is located on the frame 20 positioned above the frame nose piece 22. The container 12 has a fluid port 24 for filling and emptying. By way of example, the capacity of the illustrated container 12 is 10 ml to 20 ml.

15

The fluid conduits 18 extend from the container 12 to each pump 14. The illustrated conduits 18 are fluidically sealed passages incorporated within the frame eyepiece 26.

20

With reference to the diagrammatic views of FIGURES 3 and 4, each illustrated pump 14 has a chamber 44 that receives liquid to be dispensed from a fluid conduit 18. The pump dispenses the liquid from the chamber through a frontal fluid outlet 58. The illustrated pump chamber 44 is bounded by a back wall 50, a tubular side wall 48, and a front wall 46. The fluid outlet 58 is formed by a centrally-located aperture through the chamber front wall 46. The pump chamber 44 is mounted on the end of a fluid conduit 18 to receive fluid directly from the conduit through one or more small openings 54 through the chamber back wall 50.

25

The pump mechanism employs an electrical heater 52, typically a thin film electrical resistive element, located at the back of the chamber 44 and typically mounted on the chamber back wall 50 as illustrated. The heater 52 is aligned directly opposite the pump outlet 58 and is connected to the electrical control module 16 by way of electrical conductors 42.

30

As further shown in FIGURES 3 and 4, each illustrated pump 14 has a diaphragm 60, considered optional, that spans across the chamber 44 between the heating element 52 and the front wall 46 and that is apertured with one or more through passages 62 for the liquid being pumped. The diaphragm is flexible and secured, for example, to the chamber side wall 48. The apertures in the diaphragm 60

35

-8-

are not between the heating element 52 and the fluid outlet 58 but rather are radially spaced outwardly therefrom. The passages 62 in the illustrated diaphragm 60 are adjacent the periphery of the diaphragm, and the heating element 52 is located adjacent the center of the structure, as shown.

5 With further reference to FIGURE 1, the control module 16 illustratively mounts on one temple piece of the frame 20 and operates all the pumps 14 concurrently and essentially in parallel. An alternative is to provide a control module 16 that produces a selected pattern of multiple signals for operating different pumps 10 14 selectively. The illustrated control module 16, FIGURE 1, operates with a battery power source 28, illustratively carried on the other frame temple piece, and an adjustable pulse generator 30. An on-off switch 32 and a control adjustment 34 enable the user to turn the pumps off and on, and to vary the control signal to the pumps to control the fluid delivery to the eye. In particular, the control module 16 is preferably 15 arranged so that the duration and the frequency of the control signal can be selectively adjusted. In one preferred practice, the control module operates each pump 14 to expel a succession of liquid droplets, and is controllable to select the duration of each succession of droplets and to select the interval between successions. The further construction of the control module 16 and its operation with the remaining elements of 20 the system as described herein can be implemented with known skills.

In operation, and with references to FIGURES 1 and 3, liquid to be dispensed enters the chamber 44 from the fluid conduit 18 by way of the aperture 54 in the chamber back wall 50. The liquid passes through the openings 62 in the diaphragm 60 25 and hence normally substantially fills the chamber 44. The aperture forming the fluid outlet 58 is sufficiently small so that capillary forces retain the liquid within the chamber, and the liquid does not leak out under normal conditions. The pump discharges a droplet 64 of the liquid in response to an electrical signal applied from the control module 16 to the heater 52. The resultant thermal expansion of liquid 30 adjacent the heater 52, within the chamber 44, produces a vaporizing force that expels a droplet outward from the chamber through the outlet 58.

The sequential views A through E of FIGURE 5 depict this operation of the illustrated pump 14. FIGURE 5A shows the pump at rest, with the chamber 44 filled 35 with liquid 66 from the conduit 18 and a capillary meniscus at the outlet port 58. When the heater 52 becomes hot, due to an electrical signal from the control module 16, a bubble-like volume 66a of thermally expanded liquid forms adjacent the heater 52. The resultant increased pressure in the chamber 44 forces liquid outward through the fluid outlet 58, as appears in FIGURE 5B.

-9-

FIGURE 5C shows further development of the bubble-like volume 66a of thermally expanded fluid in front of the heater 52, and the correspondingly increased droplet formed at the pump fluid outlet 58. Upon further expansion of the liquid adjacent the hot heater 52, and termination of the heating signal to the heater 52 so that the thermal expansion in the liquid adjacent the heater 52 terminates, a drop 64 of the liquid is expelled outward from the outlet. FIGURE 5E shows that the pump 14 quickly resumes the quiescent condition, similar to that of FIGURE 5A with the ejected droplet directed toward the eye of the wearer of the device 10.

10

The operation of each pump 14, in response to an electrical impulse from the control unit 16, is essentially instantaneous through the successive stages shown in FIGURES 5B, 5C and 5D. The further construction of each pump 14, and its operation with the other elements of the system as described herein, can be implemented with known skills.

15

Another embodiment of the pump 14 employs a laser to heat and thereby expand the fluid in the chamber 44, FIGURES 3 and 5, in place of the resistive heating by heater 52. For example, a modulated laser beam which is absorbed and focussed at the liquid in chamber 44 will cause vaporization and ejection of fluid from outlet 58 at the the modulated frequency. Laser power and wavelength and can be used to vary the volume of ejected liquid.

20

In one illustrative embodiment, the pump parameters, including the chamber 44 volume and the outlet port 58 and the heating element 52, are selected to form each droplet with a size typically in the order of 200 picoliters. This volume is illustrative and the invention can be practiced with other parameters. By way of example, in one practice, the pumps 14 of the device 10 of FIGURE 1 deliver 200 picoliter volumes of artificial tear fluid at a rate of 100 Hz for one second of every five second interval. Typically, repetition rates between 1 and 2000 Hz are selected depending upon the fluid viscosity. These frequencies are used in conjunction with outlet apertures generally between 10 and 100 μ m to deliver, for example, 1 microliter per minute tear delivery, which is normal.

30

The optional diaphragm 60 in the pump chamber 44, FIGURES 3 and 4, can be a thermal barrier between the liquid that is dispensed from the outlet 58 and the liquid that is thermally expanded by the heater 52. The diaphragm can thus assure that the liquid the pump expels is relatively cool, and is not the hotter liquid acted on by the heater 52.

35

-10-

Among other variations with which the invention can be practiced are, as shown in FIGURE 6, a dispenser 70 that provides a system of pumps 80 connected by way of positioning tubes 78, like stalks, with a liquid container 74 and further having a control module 76. The dispenser 70 has a mounting clamp 72 for removable and replaceable mounting on a spectacle frame 82. Each pump 80 of the illustrated dispenser 70 is mounted on the distal end of a positioning tube 78. Each positioning tube preferably can be selectively flexed to position and orient the pump outlet port as desired relative to the eye of the user of the device. Each positioning tube 78 is relatively soft and readily deformed to assure that inadvertent contact of a tube or pump with the user causes no injury.

The dispenser 70, aside from being removable and replaceable relative to a spectacle frame 82, can be otherwise identical to the device 10 described above with reference to FIGURES 1 through 3.

Note that the liquid container 12 of the device 10 of FIGURE 1 and the container 74 of the FIGURE 6 dispenser 70 can be a removable and replaceable cartridge. In this alternative arrangement, the user simply fits a new cartridge of the selected liquid to the device, rather than refilling the container. When a cartridge is emptied of liquid, it is simply removed and replaced. This construction enables a device according to the invention to dispense different liquids, both with and without selected medications, as required by the medical needs of the user.

FIGURE 7 shows the structure and operation of another device 90 in which, as shown in FIGURE 8, a flexible diaphragm element 98 forms two fluidically isolated chambers 94 and 96 in each pump 92. The two chambers can contain two different fluids 100 and 102. More particularly, a rear chamber 94 can contain a fluid that is optional for the liquid-ejecting pumping operation, and a forward chamber 96 can contain a treatment fluid to be ejected to the wearer's eye.

The device 90, depicted in FIGURE 7, is in part similar in construction and operation to the device 10 of FIGURES 1-5. The device 90 has an array of pumps 92 that project fluid, a control module 104 that actuates the pumps 92, and a fluid duct 106 that has two isolated fluid passages 108 and 110, as illustrated in FIGURE 7A, for carrying fluid to the pumps 92. These elements are carried on a spectacle-like frame 112 that is worn by the patient like a conventional pair of eyeglasses.

As depicted in FIGURE 8, each illustrated pump 92 is a thermal expansion jet-

-11-

type pump and has a cylindrical sidewall 114 that is bounded by a backwall 116 and a front wall 118. The front wall 118 has a centrally-located aperture that forms a fluid outlet port 120. The pump employs an electrical heater 122, typically a thin film electrical resistive element mounted on the backwall 116 aligned opposite the fluid outlet port 120, and connected to the electrical control module 104 by way of electrical conductors (not shown).

As further shown in FIGURES 7, 7A, and 8, the device 90 has two separate containers 126 and 128 that each hold a supply of fluid. Each supply of fluid is coupled to one of the isolated passages 108 and 110 of the fluid duct 106. In the illustrated device, the container 126 is fluidically connected to the passage 108 and the container 128 is fluidically connected to the passage 110. The duct 106 couples the fluids in the containers 126 and 128 to the chambers of the pumps 92.

Each illustrated pump 92, shown in FIGURE 8, has a diaphragm 98 that spans the interior of the pump 92 and seals to the sidewall 114 to form a flexible, non-permeable barrier between the chambers 94 and 96. Each chamber couples to only one fluid passage of the fluid duct 106. In the illustrated example, the forward chamber 96 has a fluid port 130 in the sidewall 114 that couples to the passage 110 to receive fluid 102 from the container 128. Likewise, the rear chamber 94 receives fluid 100 from the container 126 through a fluid port 132 that extends through the backwall 116 and is coupled to the fluid passage 108.

Referring again to FIGURE 8, the sequentially illustrated operation of pump 92 commences as shown in FIGURE 8A with the pump at rest, with the back chamber 94 filled with the fluid 100 from the duct 108 that is fluidically coupled to the container 126, and with the front chamber 96 filled with the fluid 102 from the duct 110 that is fluidically coupled to the container 128. When the heater 122 becomes hot, due to an electrical signal from control module 104, the fluid 100 within the back chamber 94 expands, FIGURES 8B and 8C. The resultant increased pressure in the chamber 94 forces a drop 134 of the fluid 102 in the chamber 96 outward through the fluid outlet 120, appears in FIGURE 8D. FIGURE 8E shows that the pump 92 quickly resumes the quiescent condition, similar to that of FIGURE 8A, with the ejected droplet 134 directed toward the eye of the wearer of the device 90, and with the forward chamber 96 again filled with the treatment liquid 102.

Another embodiment uses a heater 122 that is heated by laser energy to transfer vaporizing energy to the working fluid 100. A laser beam focussed at the element 122 can thereby provide operating power for the pump operation that FIGURE 8

-12-

illustrates.

In another embodiment, and referring to FIGURE 1, the container 12 includes at least part of the mechanism for pumping fluid. For example, a piezoelectric crystal is coupled with the container 12 and operated by the control module 16 to create a modulated hydraulic pressure within the container 12 to eject fluid from each outlet 14. A programmable control module 16, for instance, enabled by a microprocessor chip, can vary the volume and the frequency of the ejected liquid by varying the frequency and amplitude of the drive signal to the piezoelectric crystal. Accordingly, only one pump mechanism is required for multiple outlets 14. Preferably, the fluidic tube 18 leading to each outlet 14 is tapered at the end to form a jet orifice to aid the fluidic ejection to the eye.

The configuration shown in FIGURE 1 can be embodied in still another way by installing a pressurized container 12. A micro-valve positioned at the fluid outlet of the container 12, or at each outlet 14, can replace the pumping mechanisms shown, for example, in FIG. 5. A piezoelectric crystal, which expands and contracts in response to a drive signal from control module 16, can operate as a micro-valve by releasing the pressurized fluid from the container 12. A TiNi pneumatic valve can similarly operate as a micro-valve. TiNi valves utilize a thin membrane of shape-memory alloy which normally closes the valve in a de-energized state. When the membrane is energized by responding to the control module 16, the membrane contracts and opens the valve.

One further practice according to the invention, is to control independently the pumps mounted about a single eye piece rim, to provide independent control of the rate and quantity of fluid delivered to each eye. FIGURE 9 shows a liquid-spraying device 140, here shown as an aperture ring-like support 142 with multiple stalks 146. The illustrated support 142 includes support legs for resting away from and centered over the eye 144. Multiple stalks 146 mount to the support 142, each with an associated fluid outlet 148 disposed at the distal end, and directed toward the eye 144. Each stalk 146 and outlet 148 is connected through fluid lines 150 to a container 152 which holds the fluid for application to the eye. The container 152, fluid lines 150, and stalks 146 can, in one embodiment, mount to support 142 replaceably. The support 142 also houses a control module (not shown) for providing a control signal to the pumps. The control module can be similar to the corresponding element 16 of the FIGURE 1 device 10. The fluid outlets 148 preferably operate as a pump, for example as a thermal jet pump, or can use micro-valves in combination with a pressurized or hydraulically actuated container, as described above. This embodiment can, for instance, be effectively used to administer fluid to the eye during surgery requiring eye

-13-

irrigation. A singular eye piece rim placed over the eye employs the teachings of the invention to effectively irrigate an eye, and surrounding area, under surgery.

5 It will be apparent that the embodiments of FIGURES 1, 6, and 7 can employ stalks similar to the stalks 146 of FIGURE 9. The stalks for that practice, which are preferably sufficiently flexible to avoid injury to the eye, can dispose each fluid outlet or orifice closer to the eye than mounting them directly on the spectacle frame.

10 A further embodiment employs a set of one or more stalks 146 (FIGURE 9), each with a pump element or valved outlet and each mounting a fluid outlet. This device provides irrigation, or application of drugs, toxic treatment chemicals, or growth inhibitors, with precise spatial control, as well as with the control of the droplet stream as discussed with the illustrated embodiments.

15 It will thus be seen that the invention efficiently attains the objects set forth above, among those made apparent from the preceding discussion and the drawings. In particular, the invention provides methods and apparatus for directing an air-borne liquid stream or succession of drops into the eye. Since certain changes may be made in the above construction without departing from the scope of the invention, it is
20 intended that all matter contained in the above description or shown in the accompanying drawings be interpreted as illustrative rather than in a limiting sense. One such change is to mount the electrical control module and the battery separate from the spectacle frame that carries the pump and the fluid outlets: illustratively in a pocket or on a waist strap of the wearer. A reservoir of the liquid being dispensed can
25 also be mounted separately from the spectacle frame; it preferably is under pressure to deliver the liquid, against the force of gravity, to the spectacle-mounted pump element.

30 It is also to be understood that the following claims are to cover all of the generic and specific features of the invention as described herein, and all statements of the scope of the invention which, as a matter of language, might be said to fall therebetween.

Having described the invention, what is claimed is:

-14-

Claims

1. Apparatus for the topical introduction of liquid to the eye of a person, said
5 apparatus comprising
 - (A) a container for liquid that is to be introduced to the eye of a person,
 - (B) at least one pump means having a fluid outlet and coupled with said
container to receive liquid therefrom and arranged for mounting with said container on
a spectacle-like frame with said outlet directed toward and spaced away from the eye
10 of the frame wearer,
said pump means being operable in response to a control signal for propelling
liquid, received from said container, from said outlet into the air and toward the eye,
and
 - (C) control means for generating said control signal and connected for
15 applying said control signal to said pump means, said control means being arranged
for mounting on the spectacle-like frame..
2. Apparatus according to claim 1 further comprising means for removably and
replaceably mounting said pump means and said container to a spectacle-like frame.
20
3. Apparatus according to claim 1 further comprising pump positioning means for
positioning said pump means and said outlet proximate to the eye and connected in
fluid communication between said container and said pump means.
- 25 4. Apparatus according to claim 3 wherein said positioning means is elastically
displaceable upon inadvertent contact with the eye, for protecting the eye.
5. Apparatus according to claim 1 wherein said pump means is an expansion-type
jet pump for expanding fluid within said pump means and thereby driving fluid
30 through said fluid outlet.
6. Apparatus according to claim 1 wherein said pump means has heating means
for thermally expanding fluid for expelling liquid through said fluid outlet.
- 35 7. Apparatus according to claim 6 wherein said heating means includes a thin film
resistor element.
8. Apparatus according to claim 6 further comprising means for separating liquid
being discharged from said fluid outlet from the thermally expanded fluid.

-15-

9. Apparatus according to claim 6 wherein said heating means includes a laser source for delivering thermal energy to said fluid.
- 5 10. Apparatus according to claim 6 wherein said heating means includes a laser source and an absorbing element, said laser source being arranged for heating said absorbing element and said absorbing element is arranged for heating fluid by conduction.
- 10 11. Apparatus according to claim 1 in which said pump means includes a thermal expansion-type jet pump for thermally expanding fluid and for expelling liquid through said fluid outlet, said expansion-type jet pump having diaphragm means disposed between the thermally expanded fluid and said fluid outlet.
- 15 12. Apparatus according to claim 11 in which said diaphragm means forms a first pump chamber in which fluid is expanded for pumping action and forms a second pump chamber contiguous with said first chamber and from which fluid is discharged in response to said pumping action.
- 20 13. Apparatus according to claim 12
in which said container is coupled for applying liquid therein to said second pump chamber, and
further comprising a second container for fluid and coupled with said first pump chamber.
- 25 14. Apparatus according to claim 1 wherein said control means produces said control signal to eject successive droplets of liquid from said fluid outlet, said control means being arranged for producing said control signal for producing said succession of droplets with selected duration and repetition, for controlling the quantity and rate
30 of liquid introduced to the eye.
15. Apparatus according to claim 14 wherein said rate is preferably in the range one to two thousand Hertz.
- 35 16. Apparatus according to claim 14 wherein each said droplet has approximately two hundred picoliters of fluid.
17. Apparatus according to claim 14 wherein said control means is arranged for producing said control signal intermittently and wherein said rate is approximately one

-16-

to two thousand Hertz.

18. Apparatus according to claim 1 wherein said apparatus has multiple pump means and wherein said multiple pump means are circumferentially disposed around at least one lens aperture of said spectacle-like frame.

19. Apparatus for introducing liquid to the eye of a person, said apparatus comprising

(A) a spectacle frame having a lens-mount supported by a pair of temple pieces,

(B) a container for fluid which is to be introduced into the eye of a person, said container being mounted on said spectacle frame,

(C) at least one pump means having a fluid outlet and coupled with said container to receive liquid therefrom, said pump means and outlet being mounted on said lens mount of said spectacle frame with said outlet directed toward the eye of the frame wearer,

said pump means being operable in response to a control signal for ejecting into the air liquid, received from said container, and for propelling the ejected liquid from said outlet to the eye, and

(D) control means for generating said control signal and being connected for applying said control signal to said pump means.

20. A method for introducing fluid to the eye of a person, and comprising the steps of

(A) mounting to a spectacle-like frame an electrically controllable pump means having a fluid outlet and a fluidic coupling to a reservoir of aqueous solution for positioning said pump means proximate to the eye,

(B) directing said fluid outlet of said pump means toward the eye for directing the discharge of fluid toward the eye, and

(C) providing a control means for generating an electronic signal for activating said pump means and propelling said fluid, received from said reservoir, into the air through said outlet.

-17-

21. Apparatus according to claim 1 wherein said pump means pressurizes said container in response to said control signal to propel liquid through said outlet.
22. Apparatus according to claim 1 wherein said fluid outlet includes an orifice
5 disposed proximal to and spaced from the eye.
23. Apparatus according to claim 1 wherein said control means is programmable for varying the volume of said liquid propelled to the eye in a given time interval.
- 10 24. Apparatus according to claim 21 wherein said pump means comprises at least one piezoelectric crystal for creating hydraulic pressure inside said container.
25. Apparatus according to claim 1 wherein said container comprises a pressurized vessel, and wherein said pump means comprises valve means to control liquid from
15 said vessel, said valve means being operable in response to said control signal for releasing liquid from said pressurized vessel to eject liquid through said outlet.
26. Apparatus according to claim 25 wherein said valve means comprises a micro-valve having a piezoelectric crystal actuator.
20
27. Apparatus according to claim 25 wherein said valve means comprises a shape-memory alloy for creating a micro-valve.
28. Apparatus according to claim 27 wherein said shape memory alloy is TiNi.

1/5




FIG. 1




FIG. 2




FIG. 3




FIG. 4








FIG. 6








FIG. 9

INTERNATIONAL SEARCH REPORT

national Application No

PCT/US 93/07488

A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 A61F9/00 G02C11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 A61F G02C F04B A61H F04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 145 541 (MERCK & CO) 19 June 1985	1,2,19, 22
Y	see the whole document	5-18,21, 23-28
Y	US,A,3 934 585 (D.M. MAURICE) 27 January 1976 see column 8, line 57 - column 9, line 54; figure 10	5-13,21, 23-28
Y	EP,A,0 483 469 (HEWLETT-PACKARD) 6 May 1992 see abstract; figures 1-3 see column 3, line 53 - column 4, line 7 see column 5, line 10 - line 13	7,9,10, 15,17
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"T" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

26 November 1993

Date of mailing of the international search report

28.12.93

Name and mailing address of the ISA

European Patent Office, P.O. 2818 Patentlaan 2
NL - 2280 HV Rijswijk
tel. (+31-70) 340-2040, fax. 31 651 690 nl,
fax. (+31-70) 340-3016

Authorized officer

Wolf, C

INTERNATIONAL SEARCH REPORT

National Application No.
PCT/US 93/07488

Continuation DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A,5 012 496 (R.N. WEINREB ET AL.) 30 April 1991 see abstract ---	14-17
Y	US,A,5 094 594 (T.M. BRENNAN) 10 March 1992 see column 3, line 30 - column 4, line 46 see column 5, line 54 - column 6, line 16 ---	16,24,26 3,4
Y	GB,A,2 249 405 (M. C. DUTHIE ET AL.) 6 May 1992 see abstract ---	18
Y	US,A,4 878 646 (H. EDELMAN ET AL.) 7 November 1989 see claims 1,9-11 ---	27,28
P,A	US,A,5 171 306 (V. T. VO) 15 December 1992 see abstract ---	1-4,14, 18,19,21
A	US,A,4 500 895 (R.T. BUCK ET AL.) 19 February 1985 cited in the application see the whole document ---	5-7
A	DE,B,27 17 578 (PAUL PLEIGER MASCHINENFABRIK) 2 November 1978 see column 2, line 21 - line 42 see column 4, line 17 - line 25 ---	15,17, 24,26
A	EP,A,0 224 352 (IMPERIAL CHEMICAL INDUSTRIES) 3 June 1987 -----	

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US93/07488

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 20
because they relate to subject matter not required to be searched by this Authority, namely:
Method for treatment of the human body by therapy.
Please see Rule 39.1(iv) P.C.T.
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 93/07488

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0145541	19-06-85	US-A- 4573982 JP-A- 60116371	04-03-86 22-06-85
US-A-3934585	27-01-76	CH-A- 528272 DE-A,B,C 2139653 FR-A- 2104125 GB-A- 1321506	30-09-72 17-02-72 14-04-72 27-06-73
EP-A-0483469	06-05-92	US-A- 5129794	14-07-92
US-A-5012496	30-04-91	WO-A- 9217228 US-A- 5152424	15-10-92 06-10-92
US-A-5094594	10-03-92	NONE	
GB-A-2249405	06-05-92	NONE	
US-A-4878646	07-11-89	NONE	
US-A-5171306	15-12-92	NONE	
US-A-4500895	19-02-85	DE-A- 3470868 EP-A,B 0125742 JP-A- 59207263	09-06-88 21-11-84 24-11-84
DE-B-2717578	02-11-78	NONE	
EP-A-0224352	03-06-87	AU-B- 600684 AU-A- 6453486 CA-A- 1296629 JP-A- 62142110 US-A- 4952212 US-A- 5053000	23-08-90 21-05-87 03-03-92 25-06-87 28-08-90 01-10-91